

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/10/2011 Revision date: 7/1/2022 Supersedes: 6/3/2019 Version: 5.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : STER-AHOL® WIPE
Product code : SDS VEL-039

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Wipe for use on clean room surfaces.

Restrictions on use : For professional use only

1.3. Supplier

Veltek Associates, Inc.

15 Lee Blvd

Malvern, PA 19355-1234 USA

Telephone: +1 610-644-8335 - Fax: +1 610-644-8336

E-mail: vai@sterile.com

In Canada distributed by: Canada Clean Room (CCR)

20 Cope Dr.

Kanata, ON K2M 2V8, Canada Telephone: 1-(888)-595-8070

Fisher Scientific

112 Colonnade Road

Ottawa, Ontario, Canada K2E 7L6 Telephone: 1-800-234-7437

VWR International 2360 Argentia Road

Mississauga, Ontario L5N 5Z7 Telephone: 1-800-932-5000

1.4. Emergency telephone number

Emergency number : CARECHEM 24: 1-215-207-0061

1-866-928-0789 (toll free USA) Canada: 1-800-579-7421 (toll free) Mexico: +52-55-5004-8763

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2 H225 Highly flammable liquid and vapor Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Specific target organ toxicity (single exposure) Category 1 H370 Causes damage to organs (central nervous system, optic nerve)

Full text of H statements : see section 16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US)

Hazard statements (GHS US)

: Danger

: H225 - Highly flammable liquid and vapor H319 - Causes serious eye irritation

n319 - Causes serious eye imialion

H370 - Causes damage to organs (central nervous system, optic nerve)

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, protective gloves, Long sleeved clothing.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P307+P311 - If exposed: Call a poison center/doctor.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use alcohol resistant foam, Dry powder, carbon dioxide (CO2),

Water spray to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to an authorized waste collection point.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethanol	CAS-No.: 64-17-5	61.4 - 65.2	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Isopropanol	CAS-No.: 67-63-0	3.3 - 3.7	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Methanol	CAS-No.: 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Not expected to present a significant hazard under anticipated conditions of normal use.

First-aid measures after skin contact : Take off contaminated clothing and wash before reuse. Wash skin with plenty of water. If

symptoms develop, obtain medical attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : Not an expected route of exposure.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes damage to organs (central nervous system, optic nerve).

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide. Dry powder. Water spray.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Hazardous decomposition products in case of fire : Fire may produce irritating, corrosive and/or toxic gases. Carbon monoxide. Carbon dioxide.

Hydrocarbons. Aldehydes.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Keep upwind. Exercise caution when fighting any chemical fire. Cool closed containers that are

near the source of the fire. Move containers from fire area if you can do it without risk. Do not

allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use

self-contained breathing apparatus when in close proximity to fire.

7/1/2022 (Revision date) EN (English US) 3/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Remove all sources of ignition. Ventilate area. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required. See Section 8.

Emergency procedures : Remove all sources of ignition. Use only non-sparking tools. Use special care to avoid static

electric charges. Ventilate area. Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Place in a suitable container for disposal in accordance with the waste regulations (see Section

13).

6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use only non-sparking tools. Take precautionary measures against static discharge. Avoid

contact with skin, eyes and clothing.

Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water

hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off contaminated clothing and

wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep only in the original container in a cool, well ventilated place away from: Incompatible materials. Keep container tightly closed. Keep in fireproof place. Keep out of direct sunlight.

Incompatible materials : Strong acids. Oxidizing agents. Alkali metals. Aluminum.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethanol	
ACGIH STEL (ppm)	1000 ppm	
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2022	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)			
USA - OSHA - Occupational Exposure Limits			
Local name	Ethyl alcohol (Ethanol)		
OSHA PEL (TWA) (mg/m³)	1900 mg/m³		
OSHA PEL (TWA) [2]	1000 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
Isopropanol (67-63-0)			
USA - ACGIH - Occupational Exposure Limits			
Local name	2-Propanol		
ACGIH TWA (ppm)	200 ppm		
ACGIH STEL (ppm)	400 ppm		
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI		
Regulatory reference	ACGIH 2022		
USA - ACGIH - Biological Exposure Indices			
Local name	2-PROPANOL		
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns		
Regulatory reference	ACGIH 2022		
USA - OSHA - Occupational Exposure Limits	USA - OSHA - Occupational Exposure Limits		
Local name	Isopropyl alcohol		
OSHA PEL (TWA) (mg/m³)	980 mg/m³		
OSHA PEL (TWA) [2]	400 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
Methanol (67-56-1)			
USA - ACGIH - Occupational Exposure Limits			
Local name	Methanol		
ACGIH TWA (ppm)	200 ppm		
ACGIH STEL (ppm)	250 ppm		
Remark (ACGIH)	Headache; eye dam; dizziness; nausea		
Regulatory reference	ACGIH 2022		
USA - ACGIH - Biological Exposure Indices			
Local name	METHANOL		
BEI (BLV)	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns		
Regulatory reference	ACGIH 2022		
USA - OSHA - Occupational Exposure Limits			
Local name	Methyl alcohol		
OSHA PEL (TWA) (mg/m³)	260 mg/m ³		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
OSHA PEL (TWA) [2]	200 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation. Emergency eye wash stations should be available in the immediate vicinity of any potential exposure if required by regulation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Wash hands thoroughly after handling.

Hand protection:

Wear chemically resistant protective gloves. The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed. Gloves should be removed and replaced if there are any signs of degradation or breakthrough.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Long sleeved clothing

Respiratory protection:

Not required for normal conditions of use

Thermal hazard protection:

Not required for normal conditions of use.

Other information:

Auto-ignition temperature Decomposition temperature

Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety procedures.

: No data available

: No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Polyester fabric moistened with liquid.

Color : White fabric, clear liquid

Odor : Slight Alcohol Odor threshold : No data available рН : Not applicable Melting point : Not applicable Freezing point : Not applicable Boiling point : No data available Flash point : 70.7 °F (21.5 °C) Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Highly flammable liquid. Vapor pressure : 28 mm Hg (20 °C/68 °F) Relative vapor density at 20 °C : No data available Relative density : 0.878 (Water = 1) Solubility : No data available Log Pow : No data available

7/1/2022 (Revision date) EN (English US) 6/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : Not explosive.
Oxidizing properties : Not oxidizing.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended handling and storage conditions (see section 7).

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7). Highly flammable liquid and vapor.

10.3. Possibility of hazardous reactions

Product may catch fire in close proximity to ignition source.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acids. Oxidizing agents. Alkali metals. Aluminum.

10.6. Hazardous decomposition products

Fire may produce irritating, corrosive and/or toxic gases. Carbon monoxide. Carbon dioxide. Hydrocarbons. Aldehydes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethanol (64-17-5)		
LD50 oral, rat	10470 mg/kg	
LC50 inhalation, rat (mg/l)	50000 mg/m³	
Isopropanol (67-63-0)		
LD50 oral, rat	5840 mg/kg	
LD50 dermal, rat	16.4 ml/kg	
LC50 inhalation, rat (ppm)	> 10000 ppm - 6 Hours	
Methanol (67-56-1)		
LD50 oral, rat	> 1187 mg/kg (35% Aqueous solution)	
LD50 dermal, rabbit	17100 mg/kg	
LC50 inhalation, rat (mg/l)	43.68 mg/l - 6 Hours	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation : Not classified

pH: Not applicable

Serious eye damage/irritation : Causes serious eye irritation.

pH: Not applicable

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethanol (64-17-5)

IARC group 1 - Carcinogenic to humans, (Ethanol in alcoholic beverages)

Isopropanol (67-63-0)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs (central nervous system, optic nerve).

Isopropanol (67-63-0)

STOT-single exposure May cause drowsiness or dizziness.

Methanol (67-56-1)

STOT-single exposure Causes damage to organs (optic nerve, central nervous system).

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : Causes damage to organs (central nervous system, optic nerve).

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms/effects after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ethanol (64-17-5)		
LC50 fish	11200 mg/l (calculated value)	
LC50 other aquatic organisms	4432 mg/l - 7 days (Lemna gibba)	
EC50 Daphnia	5012 mg/l (calculated value) (freshwater)	
EC50 - Crustacea [2]	857 mg/l (calculated value) (marine water)	
EC50 72h - Algae [1]	275 mg/l - 72 Hours (Chlorella vulgaris)	
NOEC (chronic)	280 mg/l - 7 days (Lemna gibba)	
NOEC chronic fish	250 mg/l - 120 Hours (Danio rerio)	
NOEC chronic crustacea	9.6 mg/l - 10 days (Ceriodaphnia dubia, reproduction)	
NOEC chronic algae	11.5 mg/l - 72 Hours (Chlorella vulgaris)	
Isopropanol (67-63-0)		
LC50 fish	9640 mg/l - 96 Hours (Pimephales promelas)	
EC50 Daphnia	> 10000 mg/l - 48 Hours (Daphnia magna)	
NOEC chronic algae	1800 mg/l - 7 days (Scenedesmus quadricauda)	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
LC50 fish	15400 mg/l 96 Hours - Lepomis macrochirus	
EC50 Daphnia	18260 mg/l 48 Hours - Daphnia magna	
EC50 96h - Algae [1]	≈ 22000 mg/l 96 Hours - Pseudokirchneriella subcapitata	

12.2. Persistence and degradability

Ethanol (64-17-5)		
Persistence and degradability	Readily biodegradable.	
Isopropanol (67-63-0)		
Persistence and degradability	Readily biodegradable.	
Biochemical oxygen demand (BOD)	1.19 g O2/g substance - 5 days (Test method EU C.5)	
Chemical oxygen demand (COD)	2.23 g O2/g substance (Test method EU C.6)	
Biodegradation	53 % - 5 days	

12.3. Bioaccumulative potential

Ethanol (64-17-5)		
Bioconcentration factor (BCF REACH)	3	
Log Pow	-0.35 (20 °C)	
Isopropanol (67-63-0)		
Log Pow	0.05 (25°C)	
Bioaccumulative potential	Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.	
Methanol (67-56-1)		
Bioconcentration factor (BCF REACH)	< 10	
Log Kow	-0.74	

12.4. Mobility in soil

Isopropanol (67-63-0)	
Ecology - soil	Miscible with water.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Manage wipes in accordance with applicable regulatory requirements.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

7/1/2022 (Revision date) EN (English US) 9/14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.1. UN number

DOT NA No : UN3175 UN-No. (TDG) : UN3175 UN-No. (IMDG) : 3175 UN-No. (IATA) : 3175

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Solids containing flammable liquid, n.o.s. (Ethanol)

Proper Shipping Name (TDG) : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Ethanol)
Proper Shipping Name (IMDG) : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Ethanol)

Proper Shipping Name (IATA) : Solids containing flammable liquid, n.o.s. (Ethanol)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 4.1 Hazard labels (DOT) : 4.1



TDG

Transport hazard class(es) (TDG) : 4.1 Hazard labels (TDG) : 4.1



IMDG

Transport hazard class(es) (IMDG) : 4.1 Hazard labels (IMDG) : 4.1



IATA

Transport hazard class(es) (IATA) : 4.1 Hazard labels (IATA) : 4.1



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3175

DOT Special Provisions (49 CFR 172.102) : 47, IB6, IP2, T3, TP33

DOT Packaging Exceptions (49 CFR 173.xxx) : 151

DOT Packaging Non Bulk (49 CFR 173.xxx) : 212

DOT Packaging Bulk (49 CFR 173.xxx) : 240

DOT Quantity Limitations Passenger aircraft/rail (49 : 15 kg

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 50 kg

CFR 175.75)

DOT Vessel Stowage Location : B

TDG

UN-No. (TDG) : UN3175
TDG Special Provisions : 16,56
Explosive Limit and Limited Quantity Index : 1 kg
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger : 15 kg

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 133

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

STER-AHOL® WIPE	
	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Specific target organ toxicity (single or repeated exposure)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

a.a. 6 6 7 7 7 a. 6 2			
Isopropanol	CAS-No. 67-63-0	3.3 - 3.7%	
Methanol	CAS-No. 67-56-1	3.0 - 3.4%	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Methanol (67-56-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations



This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Ethanol(64-17-5)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Isopropanol(67-63-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Methanol(67-56-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 07/01/2022

Data sources : US OSHA HazCom (GHS) 25 May 2012. ECHA (European Chemicals Agency),

http://echa.europa.eu/. NFPA 704, 2022 edition.

Other information : None.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H225	Highly flammable liquid and vapor	
H301	Toxic if swallowed	
H311	Toxic in contact with skin	
H319	Causes serious eye irritation	
H331	Toxic if inhaled	
H336	May cause drowsiness or dizziness	
H370	Causes damage to organs	

Abbreviations and acronyms		
	ACGIH (American Conference of Government Industrial Hygienists)	
	ATE (Acute Toxicity Estimate)	
	CAS (Chemical Abstracts Service) number	
	EC50 (Effective Concentration 50%)	
	IARC (International Agency for Research on Cancer)	
	IATA (International Air Transport Association)	
	IMDG (International Maritime Dangerous Goods Code)	
	IMO (International Maritime Organisation)	
	LC50 (Lethal Concentration 50%)	
	LD50 (Lethal Dose 50%)	
	NIOSH (National Institute for Occupational Safety and Health)	
	OECD (Organisation for Economic Co-operation and Development)	
	STEL (Short Term Exposure Limit)	
	TLV (Threshold Limit Value) (ACGIH)	
	TWA (Time Weighted Average)	
	UNxxxx (Number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods)	

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well

as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Indication of changes:				
Section	Changed item	Change	Comments	
2	Hazards identification	Modified		
3	Composition/Information on ingredients	Modified		
4	First aid measures	Modified		
5	Fire fighting measures	Modified		
6	Accidental release measures	Modified		
7	Handling and storage	Modified		
8	Exposure controls / Personal protection equipment	Modified		
9	Physical and chemical properties	Modified		
10	Stability and reactivity	Modified		
11	Toxicological information	Modified		
12.	Ecological information	Modified		
13	Disposal considerations	Modified		
15	Regulatory information	Modified		
16	Other information	Modified		

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Veltek Associates, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Veltek Associates, Inc. accepts no liability for loss or damage resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

This SDS has been translated into the official language of the country/region in which the product is to be placed on the market. Where no official translation exists, the regulatory text is reported in English, as it appears in the relevant regulatory text.