

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/22/2019 Revision date: 4/8/2022 Supersedes: 2/5/2020 Version: 3.0

# **SECTION 1: Identification**

### 1.1. Identification

Product form : Mixture

Product name : DECON-PHENE® PLUS

Product code : SDS VEL-142

# 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Disinfectant

# 1.3. Supplier

Veltek Associates, Inc.

15 Lee Blvd

Malvern, PA 19355-1234 USA

Telephone: +1 610-644-8335 - Fax: +1 610-644-8336

E-mail: vai@sterile.com

In Canada distributed by: Canada Clean Room (CCR)

20 Cope Dr.

Kanata, ON K2M 2V8, Canada Telephone: (888)595-8070

# 1.4. Emergency telephone number

Emergency number : CARECHEM 24: 1-215-207-0061

1-866-928-0789 (toll free)

Canada: 1-800-579-7421 (toll free) Mexico: +52-55-5004-8763

# **SECTION 2: Hazard(s) identification**

### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 3	H226	Flammable liquid and vapor
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity — Single exposure, Category 3,	H335	May cause respiratory irritation
Respiratory tract irritation		
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs (kidneys) through prolonged or
		repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. GHS Label elements, including precautionary statements

### **GHS US labeling**

Hazard pictograms (GHS US)











Signal word (GHS US)

Hazard statements (GHS US)

Precautionary statements (GHS US)

: Danger

: H226 - Flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure

H401 - Toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P260 - Do not breathe vapors.

P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear eye protection, face protection, protective gloves, protective clothing.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a doctor.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use Water spray, Alcohol-resistant foam, Carbon dioxide, Dry

powder to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to an authorized waste collection point.

### 2.3. Other hazards which do not result in classification

No additional information available

# 2.4. Unknown acute toxicity (GHS US)

Not applicable

# **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Clorofene (ortho-benzyl-para-chlorophenol)	CAS-No.: 120-32-1	10-15	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Biphenyl-2-ol (ortho-phenylphenol)	CAS-No.: 90-43-7	10-15	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Sulfuric acid, mono-C10-16-alkyl esters, sodium salts	CAS-No.: 68585-47-7	5 - 10	Skin Irrit. 2, H315 Eye Dam. 1, H318
Isopropanol	CAS-No.: 67-63-0	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Sodium hydroxide	CAS-No.: 1310-73-2	1 - 5	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Tetrasodium ethylene diamine tetraacetate	CAS-No.: 64-02-8	1 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318 STOT RE 2, H373
Sodium xylenesulphonate	CAS-No.: 1300-72-7	1 - 5	Eye Irrit. 2A, H319
Ethylene glycol	CAS-No.: 107-21-1	1 - 5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Sodium nitrite	CAS-No.: 7632-00-0	0.1 - 1	Ox. Sol. 2, H272 Acute Tox. 3 (Oral), H301 Eye Irrit. 2, H319 Aquatic Acute 1, H400
Benzenesulfonic acid, C10-16-alkyl derivs.	CAS-No.: 68584-22-5	0.1 - 1	Eye Irrit. 2A, H319

<sup>\*</sup>Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

# **SECTION 4: First-aid measures**

# 4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove person to fresh air and keep at rest in a position comfortable for breathing. If symptoms develop obtain medical attention.

First-aid measures after skin contact

: Immediately remove contaminated clothing or footwear. Rinse skin with plenty of water or shower. Obtain immediate medical attention.

4/8/2022 (Revision date) EN (English US) 3/17

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eve contact

: Rinse immediately with plenty of water (for at least 15 minutes). Ensure that folded skin of eyelids is thoroughly washed with water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain immediate medical attention.

First-aid measures after ingestion

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth. Give 100 - 200 ml of water to drink. Obtain immediate medical attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

: Causes severe skin burns and eye damage. May cause an allergic skin reaction. Severe irritation or burns to the mouth, throat, esophagus, and stomach. Irritation of the respiratory tract. May cause damage to organs (kidneys) through prolonged or repeated exposure. May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically. Doctor: gastric lavage is not recommended.

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Alcohol-resistant foam. Carbon dioxide. Dry powder.

Unsuitable extinguishing media : Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Hazardous decomposition products in case of fire : Fire may produce irritating, corrosive and/or toxic gases. Phenolic compounds. Carbon

monoxide. Carbon dioxide. Chlorine. Sulphur oxides.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Keep upwind. Exercise caution when fighting any chemical fire. On heating, there is a risk of

bursting due to internal pressure build-up. Cool down the containers exposed to heat with a

water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use

self-contained breathing apparatus when in close proximity to fire.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate area. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Evacuate unnecessary personnel.

# 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Use chemically protective clothing. Emergency procedures : Ventilate area. Do not breathe vapors. Do not get in eyes, on skin, or on clothing.

### 6.2. Environmental precautions

Collect spillage. Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if large amounts of the product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb spillage to prevent material-damage. Absorb with earth, sand or other non-combustible

material and transfer to containers for later disposal. Store in corrosive resistant container with a

resistant inner liner.

4/8/2022 (Revision date) EN (English US) 4/17

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Provide good

ventilation in process area to prevent formation of vapor. Do not breathe vapors. Do not get in

eyes, on skin, or on clothing.

Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial

hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before

reuse. Contaminated work clothing should not be allowed out of the workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Store in corrosive resistant container with a resistant inner liner. Keep

container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Incompatible materials : Strong oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Isopropanol (67-63-0)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Propanol	
ACGIH TWA (ppm)	200 ppm	
ACGIH STEL (ppm)	400 ppm	
Remark (ACGIH)	TLV <sup>®</sup> Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
Regulatory reference	ACGIH 2022	
USA - ACGIH - Biological Exposure Indices		
Local name	2-PROPANOL	
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure Limits		
Local name	Isopropyl alcohol	
OSHA PEL (TWA) (mg/m³)	980 mg/m³	
OSHA PEL (TWA) [2]	400 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Sodium hydroxide (1310-73-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Sodium hydroxide	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium hydroxide (1310-73-2)			
ACGIH OEL Ceiling	2 mg/m³		
Remark (ACGIH)	URT, eye, & skin irr		
Regulatory reference	ACGIH 2022		
USA - OSHA - Occupational Exposure Limits	USA - OSHA - Occupational Exposure Limits		
Local name	Sodium hydroxide		
OSHA PEL (TWA) (mg/m³)	2 mg/m³		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
Ethylene glycol (107-21-1)			
USA - ACGIH - Occupational Exposure Limits			
Local name	Ethylene glycol		
ACGIH TWA (ppm)	25 ppm		
ACGIH OEL STEL	10 mg/m³		
ACGIH STEL (ppm)	50 ppm		
Remark (ACGIH)	Kidney dam; URT & eye irr		
Regulatory reference	ACGIH 2022		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide good ventilation in process area to prevent formation of vapor. Ensure exposure is below

occupational exposure limits (where available). Emergency eye wash stations and safety

showers should be available in the immediate vicinity of any potential exposure.

: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

# 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Environmental exposure controls

Avoid all unnecessary exposure. Wear suitable protective clothing.

### Hand protection:

Wear chemically resistant protective gloves. The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed. Gloves should be removed and replaced if there are any signs of degradation or breakthrough.

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

### Thermal hazard protection:

Not required for normal conditions of use.

### Other information:

Do not eat, drink or smoke during use. Handle in accordance with good industrial hygiene and safety procedures.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Color : Amber
Odor : Slight Phenol
Odor threshold : No data available
pH : 11.75 – 13 (Concentrate)

Melting point: Not applicable.Freezing point: No data availableBoiling point: 212 °F (100 °C)

Flash point : 134 °F

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Flammable liquid and vapor.

Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density :  $1.095 - 1.112 (68 \,^{\circ}F)(Water = 1)$ 

Solubility : Soluble in water.

Water: completely soluble

Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** No data available Explosive properties Not explosive. Oxidizing properties : Not oxidizing.

### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Stable under recommended handling and storage conditions (see section 7).

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

Flammable liquid and vapor.

#### 10.4. Conditions to avoid

Extremely high or low temperatures.

# 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Fire may produce irritating, corrosive and/or toxic gases. Carbon monoxide. Carbon dioxide. Phenolic compounds. Chlorine. Sulphur oxides.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 11: Toxicological information**

5201014 11. Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral) :	Not classified
Acute toxicity (dermal) :	Not classified
,	Not classified
DECON-PHENE® PLUS	
LD50 oral, rat	4228 mg/kg (Rat)
Isopropanol (67-63-0)	
LD50 oral, rat	5840 mg/kg
LD50 dermal, rat	16.4 ml/kg
LC50 inhalation, rat (ppm)	> 10000 ppm - 6 Hours
Clorofene (ortho-benzyl-para-chlorophenol) (	120-32-1)
LD50 oral, rat	4147 mg/kg
LD50 dermal, rat	> 2000 mg/kg
LC50 inhalation, rat (mg/l)	2.5 mg/l - 4 Hours
Tetrasodium ethylene diamine tetraacetate (6	4-02-8)
LD50 oral, rat	1780 – 2000 mg/kg
Sodium nitrite (7632-00-0)	
LD50 oral, rat	180 mg/kg
ATE US (oral)	180 mg/kg body weight
Ethylene glycol (107-21-1)	
LD50 oral, rat	7712 mg/kg
LC50 inhalation, rat (mg/l)	> 2.5 mg/l - 6 Hours (mist)
Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)	
LD50 oral, rat	2733 mg/kg
LD50 dermal, rabbit	> 2000 mg/kg
LC50 inhalation, rat (mg/l)	> 949 mg/m³ - 1 Hours
Skin corrosion/irritation :	Causes severe skin burns. pH: 11.75 – 13 (Concentrate)
Serious eye damage/irritation :	Causes serious eye damage.
Description or akin consistration	pH: 11.75 – 13 (Concentrate)
	May cause an allergic skin reaction.  Not classified
S ,	Not classified  Not classified
Isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)	
IARC group	3 - Not classifiable
Reproductive toxicity :	Not classified
STOT-single exposure :	May cause respiratory irritation.

4/8/2022 (Revision date) EN (English US) 8/17

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1		
Isopropanol (67-63-0)		
STOT-single exposure	May cause drowsiness or dizziness.	
Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure :	May cause damage to organs (kidneys) through prolonged or repeated exposure.	
Clorofene (ortho-benzyl-para-chlorophenol) (120-32-1)		
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure.	
Tetrasodium ethylene diamine tetraacetate (64-02-8)		
STOT-repeated exposure	May cause damage to organs (respiratory tract) through prolonged or repeated exposure (Inhalation).	
Ethylene glycol (107-21-1)		
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).	
Viscosity, kinematic :	Not classified No data available Causes severe skin burns and eye damage. May cause an allergic skin reaction. Severe	
symptoms	irritation or burns to the mouth, throat, esophagus, and stomach. Irritation of the respiratory tract. May cause damage to organs (kidneys) through prolonged or repeated exposure. May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).	

# SECTION 12: Ecological information

# 12.1. Toxicity

Isopropanol (67-63-0)		
LC50 fish	9640 mg/l - 96 Hours (Pimephales promelas)	
EC50 Daphnia	> 10000 mg/l - 48 Hours (Daphnia magna)	
NOEC chronic algae	1800 mg/l - 7 days (Scenedesmus quadricauda)	
Clorofene (ortho-benzyl-para-chlorophenol) (1	20-32-1)	
LC50 fish	1.5 mg/l - 96 Hours (Danio rerio)	
EC50 Daphnia	0.655 mg/l - 48 Hours (Daphnia magna)	
LC50 fish 2	0.33 mg/l - 96 Hours (Lepomis macrochirus)	
EC50 - Crustacea [2]	0.286 mg/l - 48 Hours (Crassostrea virginica)	
NOEC (chronic)	0.0067 mg/l - 21 days (Daphna magna, reproduction)	
NOEC chronic fish	< 0.0095 mg/l - 30 days (Danio rerio)	
Sodium hydroxide (1310-73-2)		
LC50 fish	196 mg/l 96 Hours	
EC50 Daphnia	40.4 mg/l 48 Hours (crustacea)	
LC50 fish 2	125 mg/l 96 Hours (Gambusia affinis)	
EC50 - Crustacea [2]	34.59 – 47.13 mg/l 48 Hours (Ceriodaphnia dubia)	
Sodium nitrite (7632-00-0)		
LC50 fish	0.54 – 26.3 mg/l - 96 Hours (Oncorhynchus mykiss)	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium nitrite (7632-00-0)		
LC50 other aquatic organisms	4.93 mg/l - 96 Hours (Cherax quadricarinatus)	
EC50 Daphnia	15.4 mg/l - 48 Hours (Daphnia magna, Mobility), (OECD 202 method)	
ErC50 algae	> 100 mg/l - 72 Hours (Desmodesmus subspicatus), (OECD 201 method)	
NOEC (chronic)	2 mg/l - 80 days (Penaeus monodon)	
NOEC chronic fish	1.05 mg/l - 29 days (Cyprinus carpio), (OECD 210 method)	
NOEC chronic crustacea	9.86 mg/l - 80 days (Penaeus monodon, bodyweight)	
Additional ecotox information	NOEC, algae: > 100 mg/l (72 Hours, Desmodesmus subspicatus, Growth rate (OECD 201 method))	
Ethylene glycol (107-21-1)		
LC50 fish	> 72860 mg/l - 96 Hours (Pimephales promelas)(EPA 600/4-90/027)	
EC50 Daphnia	> 100 mg/l - 48 Hours (Daphnia magna)(OECD 202 method)	
Biphenyl-2-ol (ortho-phenylphenol)	(90-43-7)	
LC50 fish	4.5 mg/l - 96 Hours (Danio rerio)	
EC50 Daphnia	2.7 mg/l - 48 Hours (Daphnia magna, Mobility)	
ErC50 algae	3.57 mg/l - 72 Hours (Pseudokirchneriella subcapitata, Growth rate), (OECD 201 method)	
NOEC (chronic)	0.009 mg/l - 21 days (Daphnia magna, reproduction), (OECD 211 method)	
NOEC chronic fish	0.036 mg/l - 21 days (Pimephales promelas, reproduction)	
NOEC chronic algae	0.468 mg/l - 72 Hours (Pseudokirchneriella subcapitata, Growth rate), (OECD 201 method)	

DECON-PHENE® PLUS		
Persistence and degradability	No information available.	
Isopropanol (67-63-0)		
Persistence and degradability	Readily biodegradable.	
Biochemical oxygen demand (BOD)	1.19 g O2/g substance - 5 days (Test method EU C.5)	
Chemical oxygen demand (COD)	2.23 g O2/g substance (Test method EU C.6)	
Biodegradation	53 % - 5 days	
Clorofene (ortho-benzyl-para-chlorophenol) (120-32-1)		
Persistence and degradability	Inherently biodegradable.	
Tetrasodium ethylene diamine tetraacetate (64-02-8)		
Persistence and degradability	Not readily biodegradable.	
Ethylene glycol (107-21-1)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	90 – 100 % - 10 days (OECD 301A method)	
Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)		
Persistence and degradability	Readily biodegradable.	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)	
Biodegradation	70.8 – 75.7 % - 28 days (OECD 301B method)

# 12.3. Bioaccumulative potential

DECON-PHENE® PLUS		
Bioaccumulative potential	No information available.	
Isopropanol (67-63-0)		
Log Pow	0.05 (25°C)	
Bioaccumulative potential	Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.	
Clorofene (ortho-benzyl-para-chlorophenol) (120-32-1)		
Log Pow	4.276 (25 °C)	
Tetrasodium ethylene diamine tetraacetate (64-02-8)		
BCF - Fish [1]	1.8 l/kg	
Log Pow	-13.17 (calculated value)	
Bioaccumulative potential	Not expected to bioaccumulate.	
Ethylene glycol (107-21-1)		
Log Pow	-1.36 (25 °C)	
Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)		
BCF - Fish [1]	21.7 (Danio rerio)	
Log Pow	3.18 (22.5 °C)(OECD 107 method)	
Bioaccumulative potential	Not expected to bioaccumulate.	

# 12.4. Mobility in soil

DECON-PHENE® PLUS		
Ecology - soil	Miscible with water.	
Isopropanol (67-63-0)		
Ecology - soil	Miscible with water.	
Clorofene (ortho-benzyl-para-chlorophenol) (120-32-1)		
Ecology - soil	Moderately soluble in water.	
Sodium nitrite (7632-00-0)		
Ecology - soil	Soluble in water.	
Ethylene glycol (107-21-1)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0 (QSAR)	
Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.4 – 2.6 (20 °C)	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

### **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

DOT NA No : UN2924 UN-No. (TDG) : UN2924 UN-No. (IMDG) : 2924 UN-No. (IATA) : 2924

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, corrosive, n.o.s. (Isopropanol, Sodium hydroxide)

Proper Shipping Name (TDG) : FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Sodium hydroxide)
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol, Sodium hydroxide)

Proper Shipping Name (IATA) : Flammable liquid, corrosive, n.o.s. (Isopropanol, Sodium hydroxide)

### 14.3. Transport hazard class(es)

### DOT

Transport hazard class(es) (DOT) : 3 (8) Hazard labels (DOT) : 3, 8



#### **TDG**

Transport hazard class(es) (TDG) : 3 (8) Hazard labels (TDG) : 3, 8



### **IMDG**

Transport hazard class(es) (IMDG) : 3 (8) Hazard labels (IMDG) : 3, 8



### IATA

Transport hazard class(es) (IATA) : 3 (8)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (IATA) : 3, 8



## 14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III
Packing group (IMDG) : III
Packing group (IATA) : III

### 14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes



Other information : No supplementary information available.

#### 14.6. Special precautions for user

DOT

UN-No.(DOT) : UN2924

DOT Special Provisions (49 CFR 172.102) : B1, IB3, T7, TP1, TP28

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A
DOT Vessel Stowage Other : 40

**TDG** 

UN-No. (TDG) : UN2924
TDG Special Provisions : 16
Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E1
Passenger Carrying Road Vehicle or Passenger : 5 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 132

#### **IMDG**

No data available

### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

DECON-PHENE® PLUS		
SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Respiratory or skin sensitization Health hazard - Specific target organ toxicity (single or repeated exposure)	

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Sodium nitrite CAS-No. 7632-00-0 0.1 - 1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Isopropanol	CAS-No. 67-63-0	1 - 5%
Sodium nitrite	CAS-No. 7632-00-0	0.1 - 1%
Ethylene glycol	CAS-No. 107-21-1	1 - 5%
Biphenyl-2-ol (ortho-phenylphenol)	CAS-No. 90-43-7	10-15%

## Sodium hydroxide (1310-73-2)

CERCLA RQ 1000 lb

### **Sodium nitrite (7632-00-0)**

CERCLA RQ 100 lb

### Ethylene glycol (107-21-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

#### 15.2. International regulations

# CANADA

# Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

# Clorofene (ortho-benzyl-para-chlorophenol) (120-32-1)

Listed on the Canadian DSL (Domestic Substances List)

#### Sulfuric acid, mono-C10-16-alkyl esters, sodium salts (68585-47-7)

Listed on the Canadian DSL (Domestic Substances List)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Tetrasodium ethylene diamine tetraacetate (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

### **Sodium nitrite (7632-00-0)**

Listed on the Canadian DSL (Domestic Substances List)

# Ethylene glycol (107-21-1)

Listed on the Canadian DSL (Domestic Substances List)

### Sodium xylenesulphonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List)

### Biphenyl-2-ol (ortho-phenylphenol) (90-43-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Benzenesulfonic acid, C10-16-alkyl derivs. (68584-22-5)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

### **National regulations**

No additional information available

### 15.3. US State regulations



This product can expose you to Biphenyl-2-ol (ortho-phenylphenol), which is known to the State of California to cause cancer, and Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations	
Isopropanol(67-63-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Sodium hydroxide(1310-73-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Sodium nitrite(7632-00-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Ethylene glycol(107-21-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Biphenyl-2-ol (ortho-phenylphenol)(90-43-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 16: Other information**

Revision date : 04/08/2022

Data sources : US OSHA HazCom (GHS) 25 May 2012. NFPA 704, 2022 edition.

Other information : This chemical is a pesticide product registered by the United States Environmental Protection

Agency and is subject to certain labeling requirements under federal pesticide law (FIERA). US

Agency and is subject to certain labeling requirements under federal pesticide law (FIFRA). US EPA Registration number: 68959-13. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-

pesticide chemicals.

Full text of H-phrases				
H225	Highly flammable liquid and vapor			
H226	Flammable liquid and vapor			
H272	May intensify fire; oxidizer			
H290	May be corrosive to metals			
H301	Toxic if swallowed			
H302	Harmful if swallowed			
H314	Causes severe skin burns and eye damage			
H315	Causes skin irritation			
H317	May cause an allergic skin reaction			
H318	Causes serious eye damage			
H319	Causes serious eye irritation			
H332	Harmful if inhaled			
H335	May cause respiratory irritation			
H336	May cause drowsiness or dizziness			
H351	Suspected of causing cancer			
H361	Suspected of damaging fertility or the unborn child			
H373	May cause damage to organs through prolonged or repeated exposure			
H400	Very toxic to aquatic life			
H401	Toxic to aquatic life			
H410	Very toxic to aquatic life with long lasting effects			

Abbreviations and acronyms	
	ACGIH (American Conference of Government Industrial Hygienists)
	ATE (Acute Toxicity Estimate)
	CAS (Chemical Abstracts Service) number
	EC50 (Effective Concentration 50%)
	IARC (International Agency for Research on Cancer)
	IATA (International Air Transport Association)
	IMDG (International Maritime Dangerous Goods Code)
	IMO (International Maritime Organisation)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms		
	LC50 (Lethal Concentration 50%)	
	LD50 (Lethal Dose 50%)	
	OECD (Organisation for Economic Co-operation and Development)	
	OSHA (Occupational Safety and Health Administration) (US)	
	PBT (Persistent, Bioaccumulative and Toxic)	
	QSAR (Quantitative Structure-Activity Relationship)	
	SADT (Self-Accelerating Decomposition Temperature)	
	STEL (Short Term Exposure Limit)	
	TSCA (Toxic Substances Control Act) (US)	
	TWA (Time Weighted Average)	
	UNxxxx (Number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods)	
	vPvB (very Persistent and very Bioaccumulative)	

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.


NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Indication of changes:				
Section	Changed item	Change	Comments	
2	Hazards identification	Modified		
3	Composition/Information on ingredients	Modified		
4	First aid measures	Modified		
5	Fire fighting measures	Modified		
9	Physical and chemical properties	Modified		
11	Toxicological information	Modified		
12.	Ecological information	Modified		
14	Transport information	Modified		
16	Other information	Modified		

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Veltek Associates, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Veltek Associates, Inc. accepts no liability for loss or damage resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

This SDS has been translated into the official language of the country/region in which the product is to be placed on the market. Where no official translation exists, the regulatory text is reported in English, as it appears in the relevant regulatory text.